

Declaration of performance

№ 071/2017

According to Construction Products Regulation EU № 305/2011

1. Unique identification code of the product-type:

SensoIRIS WS IS

2. Type Number:

SensoIRIS WS IS

Description:

Intelligent analogue addressable fire alarm wall mount

sounder and strobe with built-in isolator module

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer

Fire detection and fire alarm systems installed in and around buildings

4. Manufacturer

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

5. Trading Company

Teletek Electronics JSC 14A Srebarna Str. 1407 Sofia, Bulgaria

6. System of assessment

System 4

7. Notified Body

SGS Bulgaria EOOD Ltd BC MEGAPARK office "C", fl.6 115G bul. 'Tsarigradsko shose", 1784 Sofia, Bulgaria

Notified Body Number

2 OCC

Performed the prescribed tests and evaluation of factory production control according to system 4 and issued the following certificate

EC Certificate Number

BG13/88554.01

8. No European Technical Assessment has been issued for this product.



9. Declared performance

Essential characteristics	Performance	Harmonized technical
		specification
		EN 54-3:2001+A1:2002+A2:2006
Performance under fire condition	Pass	4.2, 4.3, 5.2, 5.3
Operational reliability	Pass	4.4, 4.5, 4.6, 5.4
Durability of operational reliability:	Pass	5.5, 5.6, 5.7, 5.8, 5.9
temperature resistance		
Durability of operational reliability:	Pass	5.8, 5.9, 5.10
humidity resistance		
Durability of operational reliability:	Pass	5.11
corrosion resistance		
Durability of operational reliability: shock	Pass	5.12 to 5.15
and vibration resistance		
Durability of operational reliability;	Pass	5.16
electrical stability		
Durability of operational reliability:	Pass	5.17
resistance to ingress		

Essential characteristics	Performance	Harmonized technical
		specification
		EN 54-17:2005+AC:2007
Performance under fire conditions	Pass	5.2
Operational reliability	Pass	4
Durability of operational reliability	Pass	5.4, 5.5
andresponse delay:		
temperature resistance		
Durability of operational reliability:	Pass	5.6, 5.7
humidity resistance		
Durability of operational reliability:shock	Pass	5.9 to 5.12
and vibration		
resistance		
Durability of operational reliability:	Pass	5.8
corrosion resistance		
Durability of operational reliability:	Pass	5.3, 5.13
electrical stability		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer by:

1407 Sofia, 14A, Srebarna Str. 15.08.2017 Yuliy Iliev

Quality Manager