

Basic unit TITANUS TOP SENS® EB



Part-No.: 801532.10


Approval: VdS


Basic device for wall mounting, pre-configured to receive up to two DM-TT-xx detector modules. The TITANUS PRO SENS® 2 EB is directly connectable to the esserbus/esserbus-PLus. The device is shipped equipped with the front foil for the double tube operation.

Quiescent current @ 24 V DC	approx. 260 mA at 9 V fan voltage
Connection terminal	max. 1,5 mm ²
Air humidity	< 95 %
Housing	ABS plastic
Color	white, similar to RAL 9018
Weight	approx. 1.35 kg
Dimensions	W: 200 mm H: 292 mm D: 113 mm

Features:

- Pre-configured for usage with two DM-TT-xx detector modules
- Optical status display for information alarm, pre-alarm, main alarm and fault indication
- Integrated bar graph display to optically indicate the current smoke level
- Ports for two suction tubes with an outside diameter of 25 mm
- Port for air return tube
- Possible two-detection-dependency as per VdS directive

 The previously required isolator and the reset PCB is no longer required to be fitted to this detector and is no longer available to order. The detector is now fitted as standard with the esserbus alarm transponder which incorporates all of the functions for which these devices provided. Isolator not included with delivery, can be optionally ordered under Part No. 788612.

 Pre-configured basic device including esserbus transponder and reset PC board as well as the front foil.