

Product data sheet uvex silv-Air 7333 FFP3 R D



Product information

Product features	<ul style="list-style-type: none"> • Particle-filtering cup shape mask with exhalation valve • Protection level FFP 3 • High-Performance, three-chamber climazone system • Innovative design with optimized shape • Flexible headband – easy to fit • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • 2 extra filters with inhalation valve for low breathing resistance and more comfort • High-quality uvex silv-Air outer material for best possible breathability • Ultra-soft, all-round sealing lip • Combination of 3D-shape and Sealing enable a perfect fit for almost any nose shape • Mask fulfils the requirements of reusability (R) and the dolomite dust test (D) 	
Materials	Headband:	textile
	Headband clips:	Polypropylene
	Sealing lip:	synthetic foam
	Nose clip:	metal
	Filter/mask:	PP, Polyester
	Valve:	PP
Weight	37 g	
Standard	EN 149:2001+ A1:2009	

Versions & Accessories

Article number	Colour/Version	Retail unit
8707.333	cup shape mask FFP3, white with three-chamber-system	3 pcs. per box
8701.011	uvex clear cleaning spray	1 can, 360ml

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (up to 100,000 F/m ²), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advice.